

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

1 Identification of substance

Trade name: SPRUCE GLOSS ORANGE ENAMEL

Product code: 0000980028

Manufacturer/Supplier: SEYMOUR OF SYCAMORE
917 Crosby Avenue
Sycamore, IL 60178
(815)-895-9101, www.seymourpaint.com

Information department: Health & Safety Department

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	acetone	R Xi, R F; R 11-36-66-67	22.35%
74-98-6	propane	R F+; R 12	18.96%
108-88-3	toluene	R Xn, R F; R 11-20	12.27%
64742-89-8	VM&P Naptha	R Xn; R 20/22	11.44%
106-97-8	n-butane	R F+; R 12	11.13%
64742-47-8	Mineral Spirits	R Xn, R F; R 11-65	4.31%
67-63-0	isopropyl alcohol	R Xi, R F; R 11-36-67	2.47%
108-65-6	PM acetate	R Xi; R 10-36	1.79%
13463-67-7	titanium dioxide	R Xi; R 37	1.25%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:

Xn Harmful
R N F+ Extremely flammable

Physical dangers:

Warning! Pressurized container. Keep away from heat, sparks, and flame.
 R 12 Extremely flammable.
 R 20 Harmful by inhalation.
 R 36/37 Irritating to eyes and respiratory system.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
 Keep out of the reach of children.

Effects of short-term overexposure:

Causes irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4):

Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (scale 0 - 4):

Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

General information:

Symptoms of poisoning may occur even after several hours. Medical observation for at least 48 hours after the accident is recommended.

After inhalation:

Supply fresh air. If necessary, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents:

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS ORANGE ENAMEL

Protective equipment: A respiratory protective device may be necessary.

(Contd. of page 1)

6 Accidental release measures

Personal safety precautions:

Wear protective equipment. Keep unprotected persons away.

Environmental safety precautions:

Do not allow product to reach sewage systems or ground water.
Inform appropriate authorities in case of seepage into water course or sewage system.

Measures for cleaning/collecting:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material.
Do not smoke. Protect from electrostatic charges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm
	Long-term value: 1188 mg/m ³ , 500 ppm
	BEI

74-98-6 propane

PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	(4508) mg/m ³ , (2500) ppm

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm
	Long-term value: 200 ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	188 mg/m ³ , 50 ppm
	Skin; BEI

106-97-8 n-butane

REL	1900 mg/m ³ , 800 ppm
TLV	1900 mg/m ³ , 800 ppm

64742-47-8 Mineral Spirits

TLV	200 mg/m ³
	As total hydrocarbon vapor; Skin; (P)

67-63-0 isopropyl alcohol

PEL	980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm
	Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm
	Long-term value: 492 mg/m ³ , 200 ppm

Protective hygienic measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

USA

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS ORANGE ENAMEL

(Contd. of page 2)

9 Physical and chemical properties:

General Information:

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)
Flash point:	-19°C (-2°F)
Ignition temperature:	365.0°C (689°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	0.9 Vol %
Upper Explosion Limit:	13.0 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	0.63 kg/l / 5.22 lb/gl
VOC in weight percent (less acetone):	62.6 %
Solids content:	15.0 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Possibility of Hazardous Reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.
Primary effect on the eye: Irritating effect.
Sensitization: No sensitizing effects known.
Additional toxicological information: Harmful

12 Ecological information

Other information: This product does not contain any chloroflouorocarbons (cfc's),chlorinated solvents, or lead. No specific ecological data is available for this product.
Aquatic toxicity: Harmful to aquatic organisms.
 Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans cannot be disposed of with regular trash. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Empty cans should be recycled.

14 Transport information:

Hazard class:	2.1
Identification number:	N/A
Label	2.1
ADR/RID class:	2 5F Gases
UN-Number:	1950
IMDG Class:	2
Packaging group:	II
EMS Number:	F-D,S-U
Marine pollutant:	No
ICAO/IATA Class:	2.1
Propper shipping name:	Aerosols, Flammable Consumer Commodity ORM-D

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS ORANGE ENAMEL

(Contd. of page 3)

15 Regulations**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 toluene

67-63-0 isopropyl alcohol

TSCA (Toxic Substances**Control Act):** All ingredients are listed.**PROPOSITION 65 Chemicals known to cause cancer:**

100-41-4 ethyl benzene

PROPOSITION 65 Chemicals known to cause reproductive toxicity:

108-88-3 toluene

Canadian WHMIS:

Class A, B5---Flammable Aerosols

EPA:

A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1 acetone D

108-88-3 toluene D

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3 toluene 3

67-63-0 isopropyl alcohol 3

13463-67-7 titanium dioxide 3

ACGIH TLVs:

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1 acetone A4

108-88-3 toluene A4

13463-67-7 titanium dioxide A4

NIOSH:

13463-67-7 titanium dioxide

USDA (United States**Department of****Agriculture):**

This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com