

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

1 Identification of substance

Trade name: SPRUCE GLOSS BROWN ENAMEL

Product code: 0000980036

Manufacturer/Supplier: SEYMOUR OF SYCAMORE
917 Crosby Avenue
Sycamore, IL 60178
(815)-895-9101, www.seymourpaint.com

Information department: Health & Safety Department

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	acetone	R Xi, R F; R 11-36-66-67	23.45%
74-98-6	propane	R F+; R 12	18.64%
106-97-8	n-butane	R F+; R 12	10.95%
108-88-3	toluene	R Xn, R F; R 11-20	10.85%
64742-89-8	VM&P Naptha	R Xn; R 20/22	9.98%
64742-47-8	Mineral Spirits	R Xn, R F; R 11-65	3.97%
67-63-0	isopropyl alcohol	R Xi, R F; R 11-36-67	2.45%
108-65-6	PM acetate	R Xi; R 10-36	1.59%
1330-20-7	xylene (mix)	R Xn; R 10-20/21-38	1.58%
7727-43-7	barium sulphate, natural	R Xi; R 37	1.3%
1309-37-1	red iron oxide pigment	R Xi; R 36/37	1.22%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:

Xn Harmful
R N F+ Extremely flammable

Physical dangers:

Warning! Pressurized container. Keep away from heat, sparks, and flame.
R 12 Extremely flammable.
R 20 Harmful by inhalation.
R 36 Irritating to eyes.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Keep out of the reach of children.

Effects of short-term overexposure:

Causes irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4):

Health = 1
Fire = 4
Reactivity = 3

HMIS-ratings (scale 0 - 4):

Health = 1
Fire = 4
Physical Hazard = 3

4 First aid measures

General information:

Symptoms of poisoning may occur even after several hours. Medical observation for at least 48 hours after the accident is recommended.

After inhalation:

Supply fresh air. If necessary, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Contact physician or poison control center.

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS BROWN ENAMEL

(Contd. of page 1)

5 Fire fighting measures

Extinguishing agents: CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment: A respiratory protective device may be necessary.

6 Accidental release measures

Personal safety precautions: Wear protective equipment. Keep unprotected persons away.

Environmental safety precautions: Do not allow product to reach sewage systems or ground water. Inform appropriate authorities in case of seepage into water course or sewage system.

Measures for cleaning/collecting: Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic charges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppm
 REL 590 mg/m³, 250 ppm
 TLV Short-term value: 1782 mg/m³, 750 ppm
 Long-term value: 1188 mg/m³, 500 ppm
 BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
 REL 1800 mg/m³, 1000 ppm
 TLV (4508) mg/m³, (2500) ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
 TLV 1900 mg/m³, 800 ppm

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm
 Long-term value: 200 ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV 188 mg/m³, 50 ppm
 Skin; BEI

64742-47-8 Mineral Spirits

TLV 200 mg/m³
 As total hydrocarbon vapor; Skin; (P)

67-63-0 isopropyl alcohol

PEL 980 mg/m³, 400 ppm
 REL Short-term value: 1225 mg/m³, 500 ppm
 Long-term value: 980 mg/m³, 400 ppm
 TLV Short-term value: 984 mg/m³, 400 ppm
 Long-term value: 492 mg/m³, 200 ppm

1330-20-7 xylene (mix)

PEL 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 (o-, m-, & p-isomers)
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS BROWN ENAMEL

(Contd. of page 2)

7727-43-7 barium sulphate, natural

PEL	15*; 5** mg/m ³ *Total dust **Respirable fraction
REL	10*; 5** mg/m ³ *Total dust **Respirable fraction
TLV	10 mg/m ³ (e)

Protective hygienic measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties:**General Information:**

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)

Flash point: -19°C (-2°F)**Ignition temperature:** 365.0°C (689°F)**Auto igniting:** Product is not self-igniting.**Danger of explosion:** Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.2 Vol %**Upper Explosion Limit:** 13.0 Vol %**Vapor Pressure:** 40 PSI, 2750 hPa**Density:** Not determined.**Specific Gravity:** Between 0.77 and 0.90 (Water equals 1.00)**VOC content:** 0.60 kg/l / 5.04 lb/gl**VOC in weight percent (less acetone):** 60.4 %**Solids content:** 18.6 %**10 Stability and reactivity:****Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.**Possibility of Hazardous****Reactions:** No dangerous reactions known.**11 Toxicological information:****Primary effect on the skin:** No irritant effect.**Primary effect on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

Harmful

12 Ecological information**Other information:** This product does not contain any chloroflouorocarbons (cfc's),chlorinated solvents, or lead. No specific ecological data is available for this product.**13 Disposal considerations****DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans cannot be disposed of with regular trash. Do not heat or cut empty containers with electric or gas torches.

(Contd. on page 4)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS BROWN ENAMEL

Recommendation: Empty cans should be recycled.

(Contd. of page 3)

14 Transport information:

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID class: 2 5F Gases
UN-Number: 1950
IMDG Class: 2
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Propper shipping name: Aerosols, Flammable
Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	toluene
67-63-0	isopropyl alcohol
1330-20-7	xylene (mix)

TSCA (Toxic Substances Control Act):

All ingredients are listed.

PROPOSITION 65 Chemicals known to cause cancer:

100-41-4	ethyl benzene
----------	---------------

PROPOSITION 65 Chemicals known to cause reproductive toxicity:

108-88-3	toluene
----------	---------

Canadian WHMIS:
EPA:

Class A, B5---Flammable Aerosols
A= Known human carcinogen B= Probable human carcinogen
C= Possible human carcinogen
D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1	acetone	D
108-88-3	toluene	D
1330-20-7	xylene (mix)	D

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	toluene	3
67-63-0	isopropyl alcohol	3
1330-20-7	xylene (mix)	3
1309-37-1	red iron oxide pigment	3

ACGIH TLVs:

A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

67-64-1	acetone	A4
108-88-3	toluene	A4
1330-20-7	xylene (mix)	A4
1309-37-1	red iron oxide pigment	A4

NIOSH:

1333-86-4	Carbon black
-----------	--------------

(Contd. on page 5)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 01/04/2005

Reviewed on 01/04/2005

Trade name: SPRUCE GLOSS BROWN ENAMEL

(Contd. of page 4)

**USDA (United States
Department of
Agriculture):**

This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com

USA