

CHEMICALS - SPRAY PAINTS



CHEMICALS - SPRAY PAINT		
DESCRIPTION	SIZE	ITEM #
Dark Green	16oz	CH18E
Orange	16oz	CH19E
Yellow	16oz	CH23E
Machinery Gray	16oz	CH56E
Aluminum Enamel	16oz	CH20L
Metallic ALuminum	16oz	CH16132
Light Gray Enamel	16oz	CH22E
Brown	16oz	CH24E
Red Enamel	16oz	CH25E
Dark Blue Enamel	16oz	CH26E
Flat White	16oz	CH30E
Gloss Black Enamel	16oz	CH33E
Gloss White Enamel	16oz	CH32E
Flat Black Enamel	16oz	CH49E
Satin Black Lacquer	16oz	CH50L
Black Hot Rod Primer	16oz	CH40L
Gray Enamel Primer	16oz	CH41E
Red Hot Enamel	16oz	CH43L
Omaha Orange MRO	20oz	CH1450OR
MRO Red Iron Oxide Primer	20oz	CH1407R
MRO Light Gray Primer	20oz	CH1431G
MRO Premium Gloss White	20oz	CH1413W
MRO Premium Gloss Black	20oz	CH1415B
MRO Flat Black	20oz	CH1433FB
MRO Gray	20oz	CH1416G
MRO Light Blue	20oz	CH1425LB
MRO Deep Blue	20oz	CH1426DB
MRO Equipment Yellow	20oz	CH1443Y
MRO Safety Red	20oz	CH1423SR
MRO Dark Green	20oz	CH1449G
Upside Down White	20oz	CH16652
Upside Down Orange	20oz	CH16658
Upside Down Hot Pink	20oz	CH20679HPF
Upside Down Fluorescent Green	20oz	CH20668FG



HAND CLEANER		
ITEM #	DESCRIPTION	SIZE
HCPJ32261	BLUE PUMICE WITH ALOE	FLAT TOP GALLON
HCPJ32016	BLUE PUMICE WITH ALOE	10 OZ SQUEEZE BOTTLE

To Order Call: 708-447-4500 or Outside Illinois 800-837-8707



CHEMICALS - AEROSOLS

DESCRIPTION	SIZE	ITEM #
Gasket Remover	18 oz	CH4MA
Penetrating Oil	18 oz	CH50250MB
Electrical Parts Cleaner	18 oz	CH52145
Glass Cleaner	18 oz	CH50320MB
Engine Degreaser	18 oz	CHS273
Silicone Spray	18 oz	CHS278
Battery Terminal Cleaner	18 oz	CHS283
Battery Terminal Coating	18 oz	CHS284
White Grease	18 oz	CH50435
Starting Fluid	11 oz	CH50275MB
Decal Remover	18 oz	CH161DA
Graffiti Remover	18 oz	CH20047
Brake Cleaner	20 oz	CH50276MB
Brake Parts Cleaner (Non-Chlorinated)	14 oz	CH50281MB
Rubberized Undercoating	16 oz	CH50924
Hi-Tack Gasket Adhesive	9 oz	CH99MA
Anti-Seize Lubricating Compound	16 oz	CH49576
WD40	11 oz	CHAWD40
WD40	1 gal	CHGWD40
PB 50 All Purpose Lubricant	8 oz	CHPB50
PB 50 All Purpose Lubricant	1 gal	CHPB50128
PB Blaster-Penetrating Oil	18 oz	CHPB
PB Blaster-Air Tool Conditioner	12 oz	CHPBATC
PB Blaster-Air Tool Oil/Lube	16 oz	CHPBATL
PB Blaster-Contact Cleaner	12 oz	CHPBCC
PB Blaster-Corrosion Stop Protectant	16 oz	CHPBCSP
PB Blaster-Extends Tool Life	12 oz	CHPBETL
PB Blaster-Garage Door Lube	12 oz	CHPBGDL
PB Blaster-Penetrating Oil	1 gal	CHPB128PB
PB Blaster-The Dry Lube (Teflon)	12 oz	CHPB16TDL
PB Blaster-Penetrating Sprayer		CHPBSPRAYER



To Order Call: 708-447-4500 or Outside Illinois 800-837-8707

CHEMICALS

ADHESIVES & SEALANTS		
DESCRIPTION	SIZE	ITEM #
HI-TACK GASKET ADHESIVE		
<ul style="list-style-type: none"> • Sets fast to seal and hold the heaviest of gaskets in place. • Resists gasoline, oil, kerosene, propane, and butane. <p>Applications: Felt, cork, metal, paper, and rubber gaskets.</p>	9 oz	CH99MA
SUPER GLUE		
Instantly bonds glass, metals, plastics and rubber. Works on aluminum, copper, brass, steel, vinyl, PVC, polyester, nylon, fiberglass and wood. Holding strength to 5000 lbs.	.10 oz Bottle	CH49403
BOLTLOCKER - BLUE MEDIUM STRENGTH (threadlocking compound)		
Fills gaps up to .006 inches. For application before assembly. Can be removed without special tools.	6 ml Bottle	CH49441
	24 ml Bottle	CH49442
	35 ml Pump Gel	CH49446
BOLTLOCKER - RED HIGH STRENGTH (threadlocking compound)		
Locks and seals metal threaded assemblies where high strength is required. Fills gaps up to .008 inches. For application before assembly. Protects against thread corrosion.	6 ml Bottle	CH49451
	24 ml Bottle	CH49452
	35 ml Pump Gel	CH49456
PIPE SEALANT WITH TEFLON		
Anaerobic sealant which chemically cures in the absence of air. Locks and seals threaded fittings. Lubricates and resists corrosion, leakage and loosening from vibration and moisture in hydraulic, pneumatic, steam and process piping. Allows final adjustments up to 24 hours after application. Seals threaded connections for air, oil, diesel fuel and hydraulic oil. Remains pliable. Temperature range -65°F to 300°F.	6 ml Tube	CH49485
	50 ml Tube	CH49486
	4 oz Brush Top	CH49494
	16 oz Brush Top	CH49495



Dynatex®

To Order Call: 708-447-4500 or Outside Illinois 800-837-8707



CHEMICALS

CHEMICALS - ADHESIVES & SEALANTS

RTV SILICONE GASKET MAKER

Forms gaskets instantly. Resists shrinking, cracking and migration caused by thermal cycling. Cures though and flexible. Resists oil, water, antifreeze and transmission fluid.







DESCRIPTION	SIZE	ITEM #
BLUE RTV SILICONE GASKET MAKER		
For valve covers, oil pans, transmission pans, rear end housing, timing chain covers, thermostat housing, water pump flanges. Works up to 500°F (260°C).	3 oz tube	CH49236
	8 oz Pressure Can	CH49276
RED RTV SILICONE GASKET MAKER		
Formulated to withstand highest operating temperatures. Safe for use on oxygen sensor equipped vehicles. Operating range to 650°F (343°C). Resists oil, water, anti-freeze and transmission fluid.	3 oz tube	CH2B
	8 oz Pressure Can	CH49272
	11 oz Cartridge	CHSCR
BLACK RTV SILICONE GASKET MAKER		
Sensor safe and manufactured to meet OEM specifications. For engines, drive train equipment and related components. Temperature resistant up to 500°F (260°C).	3 oz tube	CH16BR
	8 oz Pressure Can	CH49271
	11 oz Cartridge	CHSCBK
DYNA-GREY AND DYNA-BLACK GASKET MAKER L/V		
Sensor safe, low odor, non-corrosive sealant manufactured to meet OEM specifications. Will not leak and remains flexible. Resists oil, water, anti-freeze, grease and transmission fluid. Temperature resistant up to 500°F (260°C). Use to replace gaskets on valve covers, oil pans, transmission pans, rear-end housings, water pumps and timing chain covers.	Gray	CH47181
	Black	CH47200
GENERAL PURPOSE RTV SILICONE		
Cures at room temperature to a tough and flexible rubber. Seals and bonds terminals, connectors, mounting fixtures, mechanical gaskets, glass, metal, masonry, plastic, tile, rubber, wood and fabric. 10.3 oz Cartridge.	Clear*	CHSCC
	White*	CHSCW
	Aluminum/Gray*	CHSCA
	Blue	CHSCB
	Black	CHSCBK
	*USDA approved.	
SUPER WEATHERSTRIP & GASKET ADHESIVE		
High strength, fast drying, waterproof adhesive for holding gaskets in place and for bonding weatherstripping. Use for seat trim, headliner trim and carpeting. Bonds rubber, vinyl, metal, fabrics and glass. Resists oil and most shop and automotive fluids. Holds sanding discs. Parts can be repositioned while drying.	Black	CH49429
	Yellow	CH49430
BUTYL SEALANT		
One part rubber based sealant for use on metal, glass, masonry or wood joints requiring weather or moisture protection.	Gray	CHPB150G
	White	CHPB150W

*Material Safety Data Sheets available upon request.



To Order Call: 708-447-4500 or Outside Illinois 800-837-8707

CHEMICALS - SEALANTS & LUBRICANTS

DESCRIPTION	SIZE	ITEM #		
RUBBERIZED UNDERCOATING				
<ul style="list-style-type: none"> Seals, protects & insulates. Professional grade. Paintable. Quiets road noise. Adheres to any surface. 	16oz	CH50924		
AIR TOOL OIL AND CONDITIONER				
Specially formulated tool oil for use in all piston type and rotary air tools, as well as in-line air lubricators. Prevents rust formation in air tools while providing positive lubrication for smoother starting, longer lasting tools. Dissolves gum and sludge that reduce tools speed and power.	4 oz. Bottle	MIAOIL4OZ		
	1 Quart	MIAOIL		
	16 oz. Spray	CHPBATL		
	16 oz. Bottle	CHPBATCS		
ANTI-SEIZE & LUBRICATING COMPOUND				
Prevents seizing, fretting, pitting, galling and corrosion on all types of metal parts at temperatures between - 200°F and 2000°F (-128°C to 1093°C). Protects against corrosion between dissimilar metals. Eases assembly and disassembly. Extends part life while increasing high temperature reliability. Resists water, salt solution, and most shop and automotive fluids. Reduces coefficient of friction by a minimum of 20%. Meets MIL-907.	4oz Brush Top	CH49550		
	8oz Brush Top	CH49558		
	16oz Brush Top	CH49560		
	16oz Aerosol	CH49576		
WD-40				
<p>Prevents rust/corrosion - WD-40 stops rust corrosion. It deposits its inhibitors within the metal. Light rust and corrosion can be wiped off within minutes after application.</p> <p>Lubricates - WD-40 will not oxidize and cause delicate mechanisms to gum as will normal lubricants. It keeps lubricating quality at all temperatures, even in freezing weather.</p> <p>Penetrates - WD-40 is used to free binding and corrosion frozen parts. It is ideal for use on close tolerance fittings. There is no more effective penetrant on the market.</p> <p>Displaces moisture - WD-40 displaces moisture and has a "drying out" effect. It is particularly useful for application on electric motors. It inhibits moisture condensation and further wetting.</p>	11 oz. Can	CHAWD40		
	1 Gallon Can	CHGWD40		
	CHGWD40SPRAYER			

*Material Safety Data Sheets at www.lafasteners.com

CAULK GUN		
DESCRIPTION	ITEM #	
SKELETON FRAME CAULK GUN	CHCG	

To Order Call: 708-447-4500 or Outside Illinois 800-837-8707

